






Product card

Wall sandwich panel with concealed fastening







Technical information



Board cross-section



Joining of panels




Technical information

Core	PIR						
Density [kg/m³]	40 ± 3						
PIR panel thickness [mm]	60	80	100	120			
Weight[kg/m²]	10,6	11,5	12,3	13,2			
Effective width [mm]	1050	1050					
Total width [mm]	1102						
Min. panel length [mb]	2,5						
Max. panel length [mb]	13,5						
Outer/inner sheet thickness [mm]	0,4-0,7 / 0,4-0,7						
U-factor [W/m²K].	0,37	0,28	0,22	0,18			
Reaction to fire	B-s1,d0						
Wall resistance to external fire	EI15	EI15	EI30	EI30			
Type of profiling ext. / int.	[R], [M], [T], [F] / [M], [T], [F]						
Corrosion resistance ext. / ext.	C1, C2, C3 (C4 ÷ C5) / A1 (A2 ÷ A5)						
Standard coatings	Poliester Interior [INT], Poliester Standard [RAL], HERCULIT [HC], MULTILAYER 40 [MLT]						
Special coatings	PVDF, PUR, PVC (P), PVC (F) - FoodSafe						
Accessories	Fastening system, gaskets, flashings, lighting profiles						

Packaging of sandwich panels

Panel thickness [mm]	Modular width [mm]	Quantity of panels in a package	Quantity of packages per vehicle	Package height [mm]	Package weight[kg]	Maximum loading length [m]	Quantity of panels per vehicle [m2]
60	1050	13	6	880	2640	12	983
80	1050	15	4	1300	2600	12	756
100	1050	12	4	1300	2600	12	605
120	1050	10	4	1300	2600	12	504

External profiling




MICRO RIB [M] 23,65 mm












FLAT [F]



Internal and external profiling are available in any configuration.

Internal profiling











FLAT [F]

Coatings and colors

POLIESTER Interior [INT] - Available colors for interior cladding



POLIESTER Standard [RAL] - Available colors for exterior cladding



HERCULIT [HC]



MULTILAYER 40 [MLT] - Available colors for exterior cladding





Printing technology does not allow faithful rendering of colors. Therefore the colors shown are indicative and may differ from actual colors.



In addition, on individual order, non-standard colors and coatings are available, outside the palette shown (PVDF, PUR, PVC (P), PVC (F) - FoodSafe).

Coating parameters

Code	Coating thickness	Corrosion resistance	UV resistance	
POLIESTER Interior [INT]	15 μm	RA2	Not applicable	
POLIESTER Standard [RAL]	25 μm	RC3	RUV2	
HERCULIT [HC]	35 μm	RC4	RUV4	
MULTILAYER 40 [MLT]	40 μm	RC3	RUV3	

Notes







Modular roofing tiles
MODULAR SERIES



Compact roofing tiles
COMPACT SERIES



Steel roofing tiles **CLASSIC SERIES**



RETRO SERIES



PANEL SERIES



PV PANELS



INGURI



TRAPEZOIDAL



FLAT METAL



FLASHINGS



ACCESORIES



Roof Sandwich



Wall Sandwich



SKRIN, LINEA, SINUS



PROSYSTHERM



SERVICES



SERVICES



PERFORATION







