





# **Product card**

#### Wall sandwich panel with concealed fastening







# **Technical information**



### **Board cross-section**



## Joining of panels




### **Technical information**

Core	WOOL							
Density [kg/m³]	100 ± 10							
PIR panel thickness [mm]	80	100	120	160	180	200	220	240
Weight[kg/m²]	17,9	19,9	21,9	25,9	27,9	29,9	31,9	33,9
Effective width [mm]	1050							
Total width [mm]	1102							
Min. panel length [mb]	2,5							
Max. panel length [mb]	13,5							
Outer/inner sheet thickness [mm]	0,5-0,7 / 0,5-0,7							
U-factor [W/m²K].	0,54	0,43	0,36	0,27	0,24	0,22	0,20	0,18
Reaction to fire	Al							
Wall resistance to external fire	EI120	EI180	EI240	EI240	EI240	EI240	EI240	EI240
Type of profiling ext. / int.	[R], [M], [T], [F] / [M], [T], [F]							
Corrosion resistance ext. / ext.	C1, C2, C3 (C4 ÷ C5) / A1 (A2 ÷ A5)							
Standard coatings	Poliester Interior [INT], Poliester Standard [RAL], HERCULIT [HC], MULTILAYER 40 [MLT]							
Special coatings	PVDF, PUR, PVC (P), PVC (F) - FoodSafe							
Accessories	Fasteni	Fastening system, gaskets, flashings, lighting profiles						

## Packaging of sandwich panels

Panel thickness [mm]	Modular width [mm]	Quantity of panels in a package	Quantity of packages per vehicle	Package height [mm]	Package weight[kg]	Maximum loading length [m]	Quantity of panels per vehicle [m2]
80	1050	14	4	1220	2440	12	706
100	1050	11	4	1200	2400	12	554
120	1050	9	4	1180	2360	12	454
160	1050	7	4	1220	2440	12	353
200	1050	5	4	1100	2200	12	252
220	1050	5	4	1200	2400	12	252
240	1050	4	4	1060	2120	12	202

## **External profiling**




MICRO RIB [M] 23,65 mm











FLAT [F]



Internal and external profiling are available in any configuration.

## Internal profiling











FLAT [F]

### **Coatings and colors**

POLIESTER Interior [INT] - Available colors for interior cladding




#### POLIESTER Standard [RAL] - Available colors for exterior cladding



#### HERCULIT [HC]



#### **MULTILAYER 40 [MLT]** - Available colors for exterior cladding





Printing technology does not allow faithful rendering of colors. Therefore the colors shown are indicative and may differ from actual colors.




In addition, on individual order, non-standard colors and coatings are available, outside the palette shown (PVDF, PUR, PVC (P), PVC (F) - FoodSafe).

## **Coating parameters**

Code	Coating thickness	Corrosion resistance	UV resistance
POLIESTER Interior [INT]	15 μm	RA2	Not applicable
POLIESTER Standard [RAL]	25 μm	RC3	RUV2
HERCULIT [HC]	35 µm	RC4	RUV4
MULTILAYER 40 [MLT]	40 μm	RC3	RUV3

#### **Notes**







Modular roofing tiles
MODULAR SERIES



Compact roofing tiles
COMPACT SERIES



Steel roofing tiles **CLASSIC SERIES** 



**RETRO SERIES** 



**PANEL SERIES** 



**PV PANELS** 



INGURI



TRAPEZOIDAL



**FLAT METAL** 



**FLASHINGS** 



**ACCESORIES** 



**Roof Sandwich** 



**Wall Sandwich** 



SKRIN, LINEA, SINUS



**PROSYSTHERM** 



SERVICES



**SERVICES** 



**PERFORATION** 







